

JOB _____ ITEM # _____ QTY # _____

MODEL NUMBERS:

- | | | |
|----------------------------------|----------------------------------|----------------------------------|
| ☐ 1ATG1 | ☐ 2ATG7 | ☐ 3ATGH4 |
| ☐ 1ATG2 | ☐ 2ATG75 | ☐ 3ATGH5 |
| ☐ 1ATG3 | ☐ 2ATG8 | ☐ 3ATGH6 |
| ☐ 1ATG4 | ☐ 2ATGH1 | ☐ 3ATGH7 |
| ☐ 1ATG5 | ☐ 2ATGH2 | ☐ 3ATGH75 |
| ☐ 1ATG6 | ☐ 2ATGH3 | ☐ 3ATGH8 |
| ☐ 1ATG7 | ☐ 2ATGH4 | ☐ 4ATG1 |
| ☐ 1ATG75 | ☐ 2ATGH5 | ☐ 4ATG2 |
| ☐ 1ATG8 | ☐ 2ATGH6 | ☐ 4ATG3 |
| ☐ 1ATGH1 | ☐ 2ATGH7 | ☐ 4ATG4 |
| ☐ 1ATGH2 | ☐ 2ATGH75 | ☐ 4ATG5 |
| ☐ 1ATGH3 | ☐ 2ATGH8 | ☐ 4ATG6 |
| ☐ 1ATGH4 | ☐ 3ATG1 | ☐ 4ATG7 |
| ☐ 1ATGH5 | ☐ 3ATG2 | ☐ 4ATG75 |
| ☐ 1ATGH6 | ☐ 3ATG3 | ☐ 4ATG8 |
| ☐ 1ATGH7 | ☐ 3ATG4 | ☐ 4ATGH1 |
| ☐ 1ATGH75 | ☐ 3ATG5 | ☐ 4ATGH2 |
| ☐ 1ATGH8 | ☐ 3ATG6 | ☐ 4ATGH3 |
| ☐ 2ATG1 | ☐ 3ATG7 | ☐ 4ATGH4 |
| ☐ 2ATG2 | ☐ 3ATG75 | ☐ 4ATGH5 |
| ☐ 2ATG3 | ☐ 3ATG8 | ☐ 4ATGH6 |
| ☐ 2ATG4 | ☐ 3ATGH1 | ☐ 4ATGH7 |
| ☐ 2ATG5 | ☐ 3ATGH2 | ☐ 4ATGH75 |
| ☐ 2ATG6 | ☐ 3ATGH3 | ☐ 4ATGH8 |



1ATG, 1ATGH



2ATG, 2ATGH

SPECIFICATIONS

Models ATG unheated and ATGH heated tubular frame, mobile dish dispensers.

FRAME: The frame is constructed of 1" O.D. 16 ga. stainless steel tubing.

SHELVES: Each shelf is press formed from a single sheet of 18 ga. stainless steel. It is flanged down 1-5/16" on all four sides and formed back at a 30° angle for rigidity. Each inside corner is fitted with an ABS black plastic bracket and sleeve to accommodate an upright. The bottom shelf on all models is set 8" above the floor.

DISPENSERS: ATG models are fitted with model AT adjustable, drop-in dish dispensers. ATGH models are fitted with model ATH heated, adjustable, drop-in dish dispensers (See page D-9 for specifications of these dispensers). On heated units, the dispensers plug into a central junction box which is fitted with a 4' long, 3 wire cord set with NEMA 5-15P plug for 120 volt or NEMA 6-15P for 220 volt.* These units are also available for oval platters, Model ATDO.

CASTERS: Units are mounted on four, 4" diameter heavy duty, swivel casters with non-marking rubber tires.

Model #	Dish Sizes	A	B	C
1ATG1	5.125" Max.	14"	14"	36"
1ATG2	5.25" to 5.875" Max.	14"	14"	36"
1ATG3	6" to 6.625" Max.	17"	17"	36"
1ATG4	6.75" to 7.375" Max.	17"	17"	36"
1ATG5	7.5" to 8.25" Max.	17"	17"	36"
1ATG6	8.375" to 9.25" Max.	19"	19"	36"
1ATG7	9.375" to 10.25" Max.	19"	19"	36"
1ATG75	10.375" to 11.25" Max.	19"	19"	36"
1ATG8	11.375" to 12" Max.	21"	21"	36"
1ATGH1	5.125" Max.	14"	14"	36"
1ATGH2	5.25" to 5.875" Max.	14"	14"	36"
1ATGH3	6" to 6.625" Max.	17"	17"	36"
1ATGH4	6.75" to 7.375" Max.	17"	17"	36"
1ATGH5	7.5" to 8.25" Max.	17"	17"	36"
1ATGH6	8.375" to 9.25" Max.	19"	19"	36"
1ATGH7	9.375" to 10.25" Max.	19"	19"	36"
1ATGH75	10.375" to 11.25" Max.	19"	19"	36"
1ATGH8	11.375" to 12 Max.	21"	21"	36"
2ATG1	5.125" Max.	24"	14"	36"
2ATG2	5.25" to 5.875" Max.	24"	14"	36"
2ATG3	6" to 6.625" Max.	30"	17"	36"
2ATG4	6.75" to 7.375" Max.	30"	17"	36"
2ATG5	7.5" to 8.25" Max.	30"	17"	36"

SPEC E-18

Model #	Capacity	A	B	C
2ATG6	8.375" to 9.25" Max.	34"	19"	36"
2ATG7	9.375" to 10.25" Max.	34"	19"	36"
2ATG75	10.375" to 11.25" Max.	34"	19"	36"
2ATG8	11.375" to 12 Max.	38"	21"	36"
2ATGH1	5.125" Max.	24"	14"	36"
2ATGH2	5.25" to 5.875" Max.	24"	14"	36"
2ATGH3	6" to 6.625" Max.	30"	17"	36"
2ATGH4	6.75" to 7.375" Max.	30"	17"	36"
2ATGH5	7.5" to 8.25" Max.	30"	17"	36"
2ATGH6	8.375" to 9.25" Max.	34"	19"	36"
2ATGH7	9.375" to 10.25" Max.	34"	19"	36"
2ATGH75	10.375" to 11.25" Max.	34"	19"	36"
2ATGH8	11.375" to 12 Max.	38"	21"	36"
3ATG1	5.125" Max.	31"	19"	36"
3ATG2	5.25" to 5.875" Max.	31"	19"	36"
3ATG3	6" to 6.625" Max.	39"	23"	36"
3ATG4	6.75" to 7.375" Max.	39"	23"	36"
3ATG5	7.5" to 8.25" Max.	39"	23"	36"
3ATG6	8.375" to 9.25" Max.	44"	26"	36"
3ATG7	9.375" to 10.25" Max.	44"	26"	36"
3ATG75	10.375" to 11.25" Max.	44"	26"	36"
3ATG8	11.375" to 12 Max.	48"	29"	36"
3ATGH1	5.125" Max.	31"	19"	36"
3ATGH2	5.25" to 5.875" Max.	31"	19"	36"
3ATGH3	6" to 6.625" Max.	39"	23"	36"
3ATGH4	6.75" to 7.375" Max.	39"	23"	36"
3ATGH5	7.5" to 8.25" Max.	39"	23"	36"
3ATGH6	8.375" to 9.25" Max.	44"	26"	36"
3ATGH7	9.375" to 10.25" Max.	44"	26"	36"
3ATGH75	10.375" to 11.25" Max.	44"	26"	36"
3ATGH8	11.375" to 12 Max.	48"	29"	36"
4ATG1	5.125" Max.	24"	24"	36"
4ATG2	5.25" to 5.875" Max.	24"	24"	36"
4ATG3	6" to 6.625" Max.	30"	30"	36"
4ATG4	6.75" to 7.375" Max.	30"	30"	36"
4ATG5	7.5" to 8.25" Max.	30"	30"	36"
4ATG6	8.375" to 9.25" Max.	34"	34"	36"
4ATG7	9.375" to 10.25" Max.	34"	34"	36"
4ATG75	10.375" to 11.25" Max.	34"	34"	36"
4ATG8	11.375" to 12 Max.	38"	38"	36"
4ATGH1	5.125" Max.	24"	24"	36"

Model #	Capacity	A	B	C
4ATGH2	5.25" to 5.875" Max.	24"	24"	36"
4ATGH3	6" to 6.625" Max.	30"	30"	36"
4ATGH4	6.75" to 7.375" Max.	30"	30"	36"
4ATGH5	7.5" to 8.25" Max.	30"	30"	36"
4ATGH6	8.375" to 9.25" Max.	34"	34"	36"
4ATGH7	9.375" to 10.25" Max.	34"	34"	36"
4ATGH75	10.375" to 11.25" Max.	34"	34"	36"
4ATGH8	11.375" to 12 Max.	38"	38"	36"

Options

COMMON OPTIONS		
☐	R	Rotating Bumper (Adds 5" to overall length and width)
☐	SSTC	Stainless Steel Tube Covers Per tublet
☐	WB	Two locking casters
☐	Y4	Polyurethane 4
☐	Y5	Polyurethane 5