# H | SUPPORT

### **Utility / Delivery / Carts** Stainless Steel



6-UCS-2,

4-UCS-3, 6-UCL-2

Built for heavy-duty service. Carts are available in two and three shelf models, they come with load capacities from 400 to 1000 pounds. All Piper Products are built to the highest standards of construction.

#### STANDARD FEATURES

- Reinforced handle with bumper
- Vertical bumpers on 600 lb. and 1000 lb. models
- Four swivel casters on 400 lb. models
- Two fixed and two swivel casters on 600 lb. and 1000 lb. models
- Shelves and supports all stainless steel construction
- All carts meet National Sanitation Foundation specifications

#### CONSTRUCTION

#### **All Carts**

Cart to be constructed of stainless steel. Cart handle to be constructed of one-inch diameter, 18 gauge stainless steel tube. Handles to be equipped with donut bumpers attached to cart with 14 gauge mounting brackets.

#### 400 lb. Carts

Frame to be constructed of 14 gauge stainless steel corner supports with 18 gauge shelving hemmed on all four edges. All shelves and corner supports to be tig welded at joints and corners. 12 gauge aluminized steel caster supports to run the length of the entire bottom shelf, designed for swivel plate casters.

ITEM #\_\_\_\_ QTY#

#### **MODEL NUMBER:**

☐ 4-UCS-3	☐ 6-UCM-3	☐ 1-UCM-2
☐ 4-UCM-3	☐ 6-UCL-2	☐ 1-UCM-3
☐ 6-UCS-2	☐ 6-UCL-3	☐ 1-UCL-2
☐ 6-UCS-3	☐ 1-UCS-2	☐ 1-UCL-3
	□ 1 HCC 2	

#### **DIMENSIONS:**

• 4-UCS-3 - 33" H x 15.5" W x 24" L • 4-UCM-3 - 37" H x 20" W x 30" L • 6-UCS-2 - 39.25" H x 17.5" W x 28" L • 6-UCS-3 - 39.25" H x 17.5" W x 28" L • 6-UCM-2 - 39.25" H x 23" W x 39.25" L • 6-UCL-2 - 39.25" H x 23" W x 54" L • 6-UCL-3 - 39.25" H x 32" W x 54" L • 6-UCL-3 - 39.25" H x 32" W x 54" L • 6-UCL-3 - 39.25" H x 32" W x 54" L • 1-UCS-2 - 39.25" H x 17.5" W x 28" I 6-UCL-3 - 37 .3125" H x 32" W x 54" L
 1-UCS-2 - 39.25" H x 17.5" W x 28" L
 1-UCS-3 - 39.25" H x 17.5" W x 28" L
 1-UCM-2 - 39.25" H x 23" W x 39.25" L
 1-UCM-3 - 39.25" H x 23" W x 39.25" L
 1-UCL-2 - 37.3125" H x 32" W x 54" L
 1-UCL-3 - 37.3125" H x 32" W x 54" L

#### 600 lb. Carts

Frame to be constructed of 16 gauge stainless steel 1"x1" tubing. Shelves to be constructed of stainless steel. All shelves and corner supports to be tig welded at joints and corners. Cart to include two vertical, non-marking, bumpers. Carts wheel assembly shall be constructed of 3/4" diameter, solid stainless steel axle, 12 gauge stainless steel caster supports and 8" wheels.

#### 1000 lb. Carts

Frame to be constructed of 16 gauge stainless steel 1"x1" tubing. Shelves to be constructed of stainless steel. All shelves and corner supports to be tig welded at joints and corners. Shelves to also include a 1"x1" stainless steel tube brace. Cart to include two vertical, non-marking, bumpers. Carts wheel assembly shall be constructed of 3/4" diameter, solid stainless steel axle, 12 gauge stainless steel caster supports and 8" wheels.

#### **HEAVY-DUTY CASTERS**

- Plate casters for added rigidity and stability
- 5" x 1-1/4" sealed wheels
- Delrin bearing, each with 350 lbs. capacity
   Maximum resistance to chemicals, acids, bases, alcohol, water and steam
- Maximum low temperature flexibility for superior performance, even in freezing temperatures

  Caster brakes optional







## Utility / Delivery / Carts Stainless Steel

Model #	Capacity	(A) Length	(B) Width	(C) Height	Ship Wt.(lbs)
4-UCS-3	400 lbs	24"	15.5"	33"	45
4-UCM-3	400 lbs	30"	20"	37"	80
6-UCS-2	600 lbs	28"	17.5"	39.25"	60
6-UCS-3	600 lbs	28"	17.5"	39.25"	70
6-UCM-2	600 lbs	39.25"	23"	39.25"	80
6-UCM-3	600 lbs	39.25"	23"	39.25"	94
6-UCL-2	600 lbs	54"	32"	39.25"	109
6-UCL-3	600 lbs	54"	32"	37 .3125"	135
1-UCS-2	1000 lbs	28"	17.5"	39.25"	100
1-UCS-3	1000 lbs	28"	17.5"	39.25"	120
1-UCM-2	1000 lbs	39.25"	23"	39.25"	142
1-UCM-3	1000 lbs	39.25"	23"	39.25"	175
1-UCL-2	1000 lbs	54"	32"	37.3125"	155
1-UCL-3	1000 lbs	54"	32"	37.3125"	185

