



### Internal Fitting

- Internal bumpers in stainless steel to prevent damage by trolleys.
- External guards in stainless steel to prevent damage to control panel.

### Cooling Unit

- Remote condensing unit and possibility to have stainless steel protective cover
- Evaporator fitted with high flow rate fan for maximum cooling efficiency
- Ecological refrigerant R404A.

JOB \_\_\_\_\_ ITEM # \_\_\_\_\_ QTY # \_\_\_\_\_

### MODEL NUMBER:

- ☐ RCM054      ☐ RCR054S      ☐ RCM054S  
☐ RDR054S      ☐ RDM054S

### DIMENSIONS:

- RCM054 - 33.46"H x 33.46"D X L
- RDR054S - 33.5"H x 33.5"D X L
- RCR054S - 33.5"H x 33.5"D X L
- RDM054S - 33.5"H x 33.5"D X L
- RCM054S - 33.5"H x 33.5"D X L

### General Features

- Outside stainless steel Scotch-Brite finish
- Inside stainless steel with rounded corners
- Inside bottom and floor die-formed leakproof
- Insulation in high-density (93 lbs approx.) expanded polyurethane CFC and HCFC-free, thickness 3.15"
- Copper evaporator coil with aluminum fins protected against corrosion with an electronically applied epoxy paint 20 microns thick
- Anti-condensation heating element fitted on the door under the gasket
- Horizontal ergonomic handle with inside security lock
- Door with rubber sweeper gasket with closing hinges
- Heated core probe in blast freezer for an easy extraction
- Door with lock
- Electro-Fin (coating to protect fins from corrosion)

### Control, Monitoring and Safety Devices

- Electronic control board equipped with display, which shows the status of the appliance in every moment.
- The microprocessor is able to memorize till 100 programs.
- The "T" electronic control can memorize eventual alarms, and can control up to 4 core probes or 4 sensors Defrosting with activation of an electric heating element fitted on the evaporator.
- Compressor protected by overload cut-out with automatic reset Microswitch cuts out the evaporator fan and compressor when the door is opened.

### Versions / Optional Accessories

- Water cooling unit
- 2-door version (Roll-Trough)
- Version without floor (with rubber sweeper gasket)
- Condensing unit
- Cover for condensing unit
- UV sterilization system
- Printer kit

### Warranty

- One year parts and labor. Warranty is detailed on inside front cover of the price list.

S | SHOCK FREEZERS /  
BLAST CHILLERS

Countertop Side Load 054  
Shock Freezer/Blast Chiller

Model #	Description	Width	Height	Depth	Ship Wt. (lbs)
RCM054	Shock Freezers/Blast Chillers Side Load	33.46"	33.46"	29.92"	254
RDR054S	BLAST CHILLER SIDE LOADER	33.5"	33.5"	29.9"	
RCR054S	BLAST CHILLER SIDE LOADER	33.5"	33.5"	29.9"	
RDM054S	SHOCK FREEZER/BLAST CHILLERS SIDE LOADER	33.5"	33.5"	29.9"	
RCM054S	SHOCK FREEZER/BLAST CHILLERS SIDE LOADER	33.5"	33.5"	29.9"	

Part #	Description	Part #	Description
<input type="checkbox"/> RT-64	Polyurethane Caster, set of 4. Caster Diameter 2.36	<input type="checkbox"/> RXS	Time and temperature recorder with printer
<input type="checkbox"/> UV-1	Ultra Violet Sterilization	<input type="checkbox"/> USBNS	USB Connection (version S only)

SPEC S-2-B