



SK24IC-8

STANDARD FEATURES

- 304 Stainless Steel, Welded and Polished Top Assembly, Front Apron and Ends
- 304 Stainless Steel Insulated Ice Chest with 11" Inside Depth
- Factory-Installed, 4, 8 or 10 Circuit Post-Mix Sealed-In Cold Plate (Cold Plate Designated by Adding "+4", "+8", or "+10")
- Legs: Galvanized Steel Tube and Welded Cross-Brace Construction, with Corrosion Resistant Hammertone Paint and High-Impact Plastic Adjustable Feet
- Ice Chests Include 304 Stainless Steel Sliding Cover
- Standard Ice Chest: 1 1/2" Male Pipe Thread Drain
- Ice Chest with Cold Plate: 1/2" Standard Female Pipe Thread Drain
- 6" Unit Designed to Attach to Adjacent Units (No Legs)
- Constructed to Meet NSF Specifications

JOB _____ ITEM # _____ QTY # _____

MODEL NUMBER:

- ☐ SD6IC

☐ SD12IC

☐ SD18IC

☐ SD24IC

☐ SD30IC

☐ SD36IC

☐ SD48IC

☐ SK24IC

☐ SK30IC

☐ SK36IC

☐ SK48IC

☐ SD18IC (+4)

☐ SD24IC (+8, +10)

☐ SD30IC (+8, +10)

☐ SD36IC (+8, +10)

☐ SD48IC (+8, +10)

☐ SK24IC (+8, +10)

☐ SK30IC (+8, +10)

☐ SK36IC (+8, +10)

☐ SK48IC (+8, +10)

Model #	Description	L	W	H
SD6IC	Standard	19"	6"	36"
SD12IC	Standard	19"	12"	36"
SD18IC	Standard	19"	18"	36"
SD24IC	Standard	19"	24"	36"
SD30IC	Standard	19"	30"	36"
SD36IC	Standard	19"	36"	36"
SD48IC	Standard	19"	48"	36"
SK24IC	Standard	19"	24"	36"
SK30IC	Standard	19"	30"	36"
SK36IC	Standard	19"	36"	36"
SK48IC	Standard	19"	48"	36"
SD18IC (+4)	With Cold Plates	21 1/4"	18"	36"
SD24IC (+8, +10)	With Cold Plates	21 1/4"	24"	36"
SD30IC (+8, +10)	With Cold Plates	21 1/4"	30"	36"
SD36IC (+8, +10)	With Cold Plates	21 1/4"	36"	36"
SD48IC (+8, +10)	With Cold Plates	21 1/4"	48"	36"
SK24IC (+8, +10)	With Cold Plates	21 1/4"	24"	36"
SK30IC (+8, +10)	With Cold Plates	21 1/4"	30"	36"
SK36IC (+8, +10)	With Cold Plates	21 1/4"	36"	36"
SK48IC (+8, +10)	With Cold Plates	21 1/4"	48"	36"